

## WHAT IS CLAIMED IS:

- Sub A1
1. A lid and resealable tab for a drinking cup comprising a lid having
- an outer edge having a generally circular periphery;
  - a top surface for defining a drinking opening having a predetermined shape and dimension;
  - an annular side wall operatively connected to and extending from said outer edge and in a selected direction relative to said top surface;
  - an annular mounting member formed on said sidewall for sealingly engaging a lip of a drinking cup;
  - a resealable tab having
    - a relatively thin, flexible substrate having a first surface and a second surface, said substrate having a shape and dimension which is configured to cover said drinking opening with either one of said first surface and second surface; and
    - a food grade adhesive located between one of said first surface and second surface and said top surface to enable one of said first surface and second surface to be located over said drinking opening and to have said adhesive form a sealing relationship between that portion of the top surface defining

080901 5572.1 413440/021

said drinking opening and said one of said first surface and second surface.

2. The lid and resealable tab for a drinking cup of claim 1 wherein said annular sidewall selected direction is away from said top surface defining the drinking opening.

3. The lid and resealable tab for a drinking cup of claim 1 wherein said annular sidewall selected direction is towards said top surface defining the drinking opening.

4. The lid and resealable tab for a drinking cup of claim 1 wherein said adhesive is coated on one said first surface and second surface and said one of said first surface and second surface is affixed to the drinking opening to expose the remaining portion of the adhesive to the drinking opening located in the top surface.

5. The lid and resealable tab for a drinking cup of claim 1 wherein said adhesive is coated on said top surface and said one of the first surface and second surface is affixed to the adhesive coated on that portion of the top surface surrounding the drinking opening.

005527606.080901

**SECRET**

10. A resealable tab adapted to seal a drinking opening formed in a lid for a drinking cup said resealable tab comprising.

a food grade adhesive located between one of said first surface and second surface and said top surface to enable one of said first surface and second surface to be located over said

drinking opening wherein said adhesive forms a sealing layer of a predetermined thickness between that portion of the top surface defining said drinking opening and said one of said first surface and second surface, the spacing therebetween being determined by the thickness of said adhesive sealing layer.

11. The resealable tab of claim 10 wherein said food grade adhesive comprises a polyurethane composition.

12. The resealable tab of claim 10 wherein said food grade adhesive comprises a composition which has increased adhesivity as the temperature thereof is increased above ambient temperature.

13. The resealable tab of claim 10 wherein said lid includes an annular sidewall which extend, in a selected direction which is away from said top surface defining the drinking opening.

14. The resealable tab of claim 10 wherein said lid includes an annular sidewall which extends in a selected direction which is towards said top surface defining the drinking opening.

15. The lid and resealable tab for a drinking cup of claim 10 wherein said adhesive is coated on one said first surface and

second surface and said one of said first surface and second surface is affixed to the drinking opening.

16. The resealable tab of claim 10 wherein said adhesive is coated on said top surface and said one of the first surface and second surface is affixed to the adhesive coated on that portion of the top surface surrounding the drinking opening.

17. The resealable tab of claim 10 wherein said substrate is generally oval in shape.

18. The resealable tab of claim 10 wherein substrate is generally circular in shape.

19. The resealable tab of claim 17 wherein said generally oval shaped substrate has a lifting member.

20. The resealable tab of claim 17 wherein and generally oval shaped substrate has a protruding lifting member.

21. The resealable tab of claim 18 wherein said generally circular shaped substrate has a lifting member.

22. The resealable tab of claim 18 wherein said generally circular shaped substrate has a protruding lifting member.

23. In combination,

a drinking cup having a lip defining a top opening;

a lid having

080901 5572.1 413440/021

an outer edge having a generally circular periphery;  
top surface for defining a drinking opening having a  
predetermined shape and dimension;

an annular side wall operatively connected to and  
extending from said outer edge and in a selected direction  
relative to said top surface;

an annular mounting member formed on said sidewall for  
sealingly engaging the lip of the drinking cup;

a resealable tab having

a flexible substrate having a first surface and second  
surface, said substrate having a shape and dimension which is  
adapted to cover said drinking opening with either one of said  
first surface and second surface; and

a food grade adhesive located between one of said  
first surface and second surface and said top surface to enable  
one of said first and second surfaces to be located over said  
drinking opening and to have said adhesive form a sealing  
relationship between that portion of the top surface defining  
said drinking opening and said one of said first surface and  
second surface.

080901 5572.1 413440/021

24. The combination of claim 23 wherein said annular sidewall selected direction is away from said top surface defining the drinking opening.

25. The combination of claim 23 wherein said annular sidewall selected direction is towards said top surface defining the drinking opening.

26. The combination of claim 23 wherein said adhesive is coated on one said first surface and second surface and said one of said first surface and second surface having said adhesive coated thereon is affixed to the drinking opening.

27. The combination of claim 23 wherein said adhesive is coated on said top surface and said one of the first surface and second surface is affixed to the adhesive coated on that portion of the top surface surrounding the drinking opening.

28. The combination of claim 23 wherein said food grade adhesive comprises a polyurethane composition.

29. The combination of claim 23 wherein said food grade adhesive comprises a composition which has increased adhesivity as the temperature thereof is increased above ambient temperature.

30. A lid and tab for a container comprising  
a lid having

an outer edge having a generally circular periphery;

a top surface for defining an orifice having a  
predetermined shape and dimension;

an annular side wall operatively connected to and  
extending axially from said outer edge and in a first direction  
relative to said top surface;

an annular mounting member formed on said sidewall for  
sealingly engaging a lip of a container;

a resealable tab having

a relatively thin, flexible substrate having a first  
surface and second surface, said substrate having a shape and  
dimension which is adapted to cover said orifice with either one  
of said first surface and second surface; and

a food grade adhesive located between one of said  
first surface and second surface and said top surface to enable  
one of said first surface and second surface to be located over  
said orifice and to have said adhesive form a sealing  
relationship between that portion of the top surface defining

05527506-080901



said orifice and said one of said first surface and second surface.

31. A method for preventing spilling of a fluid from a drinking cup having a top surface defining a drinking opening comprising the step of:

affixing a resealable tab which is configured to cover said drinking opening wherein said resealable tab has a relatively thin, flexible substrate and a first surface and a second surface wherein said substrate has a shape and dimension to cover said drinking opening with either one of said first surface and second surface, and wherein at least one of said first surface, said second surface and said top surface has a food grade adhesive located thereon to enable said adhesive to form a sealing relationship between that portion of the top surface defining said drinking opening and at least one of said first surface and second surface.

32. The method of claim 31 wherein the step of affixing includes a resealable tab having said adhesive located on at least one of said first surface and said second surface which forms a sealing relationship with the top surface defining said drinking opening.

33. The method of claim 31 wherein the step of affixing includes said top surface having said adhesive located which forms a sealing relationship with at least one of said first surface and said second surface.

34. The method of claim 31 wherein said step of affixing includes a food grade adhesive.

35. The method of claim 34 wherein the step of affixing includes a food grade adhesive comprising a polyurethane composition.

36. The method of claim 34 wherein the step of affixing includes a food grade adhesive comprising a composition which has increased adhesivity as the temperature thereof is increased above ambient temperature.

261 5572.1claim2

00927606-000901